



United Technologies

D E S I G N I N G   I N N O V A T I V E   S O L U T I O N S

AIR CONDITIONING AND HEATING SOLUTIONS

# EFFICIENCY **OR** ADAPTABILITY ?

AQUASNAP® WITH GREENSPEED® INTELLIGENCE,  
BECAUSE YOU SHOULD NOT HAVE TO CHOOSE.



Air-cooled liquid chillers and heat pumps

Inverter 17 kW – 21 kW

**30RBV & 30RQV**



# AquaSnap® with Greenspeed® intelligence, because you should not have to choose

## EFFICIENCY

The commitment to performance

### ■ Large operating map

Equipped with the latest variable speed inverter twin rotary compressor, the AquaSnap® with Greenspeed® intelligence offers a **wide operating range of 15 to 100%**, allowing an operating outside temperature from -20°C to +46°C. The maximum **water outlet temperature can be up to 60°C** to ensure reliable heating functionality for commercial and residential buildings.

### ■ Energy savings

The smart coordination between the twin-rotary inverter compressor, the electronic expansion valve and the fan optimises the performance of the AquaSnap.

With an European **Seasonal Energy Efficiency Ratio (ESEER) up to 4.56** and a **Seasonal Coefficient of Performance (SCOP) up to 3.1**, AquaSnap with Greenspeed intelligence is the best value for air conditioning and heating solution in commercial and residential applications.

### ■ Advanced control

The **new generation of control, NHC**, perfectly meets the thermal needs of residential and commercial buildings while insuring the energy efficiency optimisation.

NHC integrates domestic hot water production and master-slave configuration up to 4 units, with JBUS connection.

#### 30RBV



ESEER up to **4.56** \*  
EER up to **4** \*\*



#### 30RQV



Energy Labelling **A+**  
SCOP up to **3.1** \*\*\*

\* Values in accordance with standard EN14511-3:2013

\*\*EER calculated for typical air-conditioning application, evaporator water entering/leaving temperature 23°C/18°C, outside air temperature 35°C

\*\*\* In accordance with standard EN 14825:2013, Average climate

&

## ADAPTABILITY

Fast to install, easy to maintain

### ■ A plug and play solution

With its complete factory wiring, **easy handling features, factory-installed options** and intuitive interface, the 30RBV and 30RVQ set up is fast and straightforward. **Its compact size allows easy integration** for small offices, hotels and shops. The AquaSnap unit can be easily integrated into an existing Building Management System (BMS). Control options are compatible with most standard communication protocols (JBUS, BACnet and LON).

### ■ Maintenance made simple

Maintaining the AquaSnap air-cooled chiller is as simple as installing it. To get direct access to all components, **all you need to do is remove the front panels.**

Furthermore, the control system stores all operating data and offers 3 specific access levels (end-user, installer and factory) to quickly provide the requested and dedicated data.

### ■ Perfect integration

Due to Carrier expertise in vibration optimisation, the AquaSnap offers an outstanding **acoustic comfort for noise sensitive environment.** With their neutral color, RAL7035, the 30RBV and 30RQV can be integrated into every environment.

**FULLY  
INTEGRATED  
OPTIONS FOR FAST  
INSTALLATION AND  
SPACE SAVINGS**

**INSTALLER DEDICATED  
CONTROL INTERFACE  
ACCESS FOR FAST AND  
EFFICIENT COMMISSIONING  
AND MAINTENANCE**

**DESIGNED FOR  
THE HIGHEST  
SOUND CONTROL  
AND VISUAL  
INTEGRATION**

# Technical Insight

## Air-cooled liquid chillers and heat pumps with Greenspeed intelligence

### 30RBV - 30RQV



#### USER INTERFACE

- Large user-friendly backlit screen
- 3 access levels: end-user, installer and factory

#### CONTROL

- Master-slave configuration up to 4 units
- Domestic hot water production and management
- JBUS connection

#### HYDRONIC MODULE

- Hydronic module with variable speed water pump (optional)



#### VARIABLE-SPEED INVERTER TWIN-ROTARY COMPRESSOR

- Pulse width modulation (PWM): fine-tuning of the compressor speed to avoid temperature fluctuation
- Efficient coordination between expansion valves, compressor, fan and control

### KEY BENEFITS

- **High performance:** twin rotary compressor and control integration
- **Advanced control:** optimised user interface, 3 comfort modes, domestic hot water production, JBUS connection...
- **Flexibility:** large operating envelope (from - 20° C to + 30°C in heating mode and from 0°C to + 46°C in cooling mode)
- **Easy installation and maintenance:** installer dedicated control interface access
- **Acoustic comfort:** optimised sound level through Carrier expertise in vibration

### GREENSPEED INTELLIGENCE, THE FULL MANAGEMENT OF VARIABLE-SPEED

The addition of variable-speed condenser fans and variable-speed rotary compressor allows the AquaSnap with Greenspeed intelligence to match load conditions, delivering exceptional part-load performance.

The control constantly monitors all machine parameters and precisely manages the operation of compressor, expansion devices, fans and water heat exchanger water pump.

# 30RBV & 30RQV



| Physical data                                |       |                         |       |  | 30RBV |      | 30RQV |       |
|----------------------------------------------|-------|-------------------------|-------|--|-------|------|-------|-------|
| STANDARD RANGE                               |       |                         |       |  | 17    | 21   | 17    | 21    |
| <b>COOLING</b>                               |       |                         |       |  |       |      |       |       |
| NOMINAL COOLING CAPACITY                     |       | C1*                     | kW    |  | 15.6  | 18.6 | 14.9  | 18.6  |
| ENERGY EFFICIENCY RATIO                      | EER   | C1*                     | kW/kW |  | 3.3   | 3.1  | 3.0   | 3.1   |
| EUROVENT CLASS COOLING                       |       | C1*                     |       |  | A     | A    | B     | A     |
| NOMINAL COOLING CAPACITY                     |       | C2*                     | kW    |  | 21.6  | 25.5 | 19.8  | 25.8  |
| ENERGY EFFICIENCY RATIO                      | EER   | C2*                     | kW/kW |  | 4.0   | 3.9  | 3.87  | 3.8   |
| EUROVENT CLASS COOLING                       | C2    | C2*                     |       |  | A     | A    | A     | A     |
| SEASONAL EFFICIENCY                          | ESEER |                         | kW/kW |  | 4.48  | 4.56 | 4.01  | 3.85  |
| <b>HEATING</b>                               |       |                         |       |  |       |      |       |       |
| NOMINAL HEATING CAPACITY                     |       | H1(30-35)*              | kW    |  | -     | -    | 17.1  | 21.1  |
| COEFFICIENT OF PERFORMANCE                   | COP   | H1*                     | kW/kW |  | -     | -    | 4.1   | 4.1   |
| NOMINAL HEATING CAPACITY                     |       | H2(40-45)*              |       |  | -     | -    | 16.2  | 20    |
| COEFFICIENT OF PERFORMANCE                   | COP   | H2*                     |       |  | -     | -    | 3.4   | 3.3   |
| NOMINAL HEATING CAPACITY                     |       | H3(47/55)*              |       |  | -     | -    | 15.2  | 19.1  |
| COEFFICIENT OF PERFORMANCE                   | COP   | H3*                     | kW/kW |  | -     | -    | 2.7   | 2.7   |
| SEASONAL EFFICIENCY                          | SCOP  | H3**                    |       |  | -     | -    | 3.1   | 2.9   |
| SEASONAL EFFICIENCY                          | (ηs)  | H3**                    | kW/kW |  | -     | -    | 121   | 113   |
| PRATED                                       |       | H3 (Average climate) ** | kW    |  | -     | -    | 9.5   | 15.4  |
| ANNUAL ENERGY CONSUMPTION                    |       | H3**                    | kWh   |  | -     | -    | 6269  | 10980 |
| ENERGY CLASS                                 |       | H3**                    |       |  | -     | -    | A+    | A+    |
| <b>WEIGHT AND DIMENSIONS</b>                 |       |                         |       |  |       |      |       |       |
| LENGHT                                       |       |                         | mm    |  |       | 584  |       |       |
| WIDTH                                        |       |                         | mm    |  |       | 1109 |       |       |
| HEIGHT                                       |       |                         | mm    |  |       | 1579 |       |       |
| OPERATING WEIGHT (WITH HYDRAULIC MODULE) (3) |       |                         | kg    |  |       | 230  |       |       |
| <b>SOUND POWER LEVEL</b>                     |       |                         |       |  |       |      |       |       |
| SOUND POWER LEVEL (1)                        |       | C1                      | dB(A) |  | 71    | 74   | 71    | 74    |
| Sound pressure level at 10 m (2)             |       |                         | dB(A) |  | 40    | 43   | 40    | 43    |

\* In accordance with standard EN 14511-3:2013

\*\* In accordance with standard EN 14825:2013, average climate

C1: Cooling mode conditions:evaporator water entering/leaving temperature 12°C/7°C, outside air temperature 35°C, evaporator fooling factor 0m² K/W

C2: Cooling mode conditions:evaporator water entering/leaving temperature 23°C/18°C, outside air temperature 35°C, evaporator fooling factor 0m² K/W

H1: Heating mode conditions:Water heat exchanger water entering/leaving temperature 30°C/35°C, fooling factor 0m² K/W. Outside air temperature 7°C db / 6°C wb

H2: Heating mode conditions:Water heat exchanger water entering/leaving temperature 40°C/45°C, fooling factor 0m² K/W. Outside air temperature 7°C db / 6°C wb

H3: Heating mode conditions:Water heat exchanger water entering/leaving temperature 47°C/55°C, fooling factor 0m² K/W. Outside air temperature 7°C db / 6°C wb

(1) In dB ref = 10-12 W weighting. Declared dualnumber noise emission values in accordance with ISO 4871 (with an associated uncertainty of +/-3 dB(A)). Measured in accordance with ISO 9614-1.

(2) In dB ref 20μPA, (A) weighting. Declared dualnumber noise emission values in accordance with ISO 4871 (with an associated uncertainty of +/-3 dB(A)). For information, calculated from the sound power level Lw(A).

(3) Weights are guideline only, please refer to the unit nameplate

Eurovent certified data

Eurovent certified data

## ACCESSORIES

|                                               |
|-----------------------------------------------|
| MASTER/SLAVE UP TO 4 UNITS SENSOR             |
| DOMESTIC HOT WATER MANAGEMENT SENSOR          |
| REMOTE INTERFACE WUI                          |
| ADDITIONAL OUTDOOR AMBIENT TEMPERATURE SENSOR |

## OPTIONS

|                                     |                                                |
|-------------------------------------|------------------------------------------------|
| CCN TO BACNET GATEWAY               | WATER FILLING SYSTEM                           |
| CCN TO LON GATEWAY                  | EXPANSION TANK                                 |
| LOCAL USER INTERFACE WUI            | MAIN DISCONNECT SWITCH                         |
| HYDRONIC MODULE WITH FIX SPEED PUMP | HYDRONIC MODULE WITH VARIABLE SPEED CIRCULATOR |
| ITALCOAT COIL PROTECTION            |                                                |