## UKCA – Safety declaration of conformity

## Daikin Europe N.V.

declares under its sole responsibility that the products to which this declaration relates:

MTS: UATYA(30/40/50/60/70/80/90/100/110/120/140/150/160/180/190)BBAY1\*, MTS: UATYA(30/40/50/60/70/80/90/100/110/120/140/150/160/180/190)BFC2Y1\*, MTS: UATYA(30/40/50/60/70/80/90/100/110/120/140/150/160/180/190)BFC3Y1\*,

MTO: 30\*\*\*...\*, 40\*\*\*...\*, 50\*\*\*...\*, 60\*\*\*...\*, 70\*\*\*...\*, 80\*\*\*...\*, 90\*\*\*...\*, 110\*\*\*...\*, 120\*\*\*...\*, 120\*\*\*...\*, 140\*\*\*...\*, 150\*\*\*...\*, 160\*\*\*...\*, 180\*\*\*...\*, 180\*\*\*...\*, 190\*\*\*...\*, 100\*\*\*...\* \*= , ,1,2,3,...,9

are in conformity with the following directive(s) or regulation(s), provided that the products are used in accordance with our instructions:

- S.I. 2008/1597: Supply of Machinery (Safety) Regulations 2008\*\*\*
- S.I. 2016/1091: Electromagnetic Compatibility Regulations 2016\*
- S.I. 2016/1105: Pressure Equipment (Safety) Regulations 2016\*\*

following the provisions of: BS EN 60204-1: 2018, BS EN 61000-6-3: 2021, BS EN 61000-6-2: 2019, BS EN 378-2: 2016, IEC 60335-2-40: 2018,

as amended.

<a></a>	-
<b></b>	_
<c></c>	-
<d></d>	_
<e></e>	Bureau Veritas Italia S.p.A. (NB1370)
<f></f>	н
<g></g>	-
<h></h>	III

DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN

DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN

<sup>\*</sup> as set out in <A> and judged positively by <B> according to the Certificate <C>.

<sup>\*\*</sup> as set out in the Technical Construction File <D> and judged positively by <E> (Applied module <F>) according to the Certificate <G>. Risk category <H>. Also refer to next page.

<sup>\*\*\*</sup> Daikin Europe N.V. is authorised to compile the Technical Construction File.

## UKCA – Safety declaration of conformity

continuation of previous page:

## Design Specifications of the products to which this declaration relates:

Maximum allowable pressure (PS): <K> (bar)

Minimum/maximum allowable temperature (TS\*):

- \* TSmin: Minimum temperature at low pressure side: <I > (°C)

Manufacturing number and manufacturing year: refer to model nameplate

Terrim: Minimidan temperature action procedure side. 42 ( c)	L
* TSmax: Saturated temperature corresponding with the maximum allowable pressure (PS): <b><m></m></b> (°C)	<n></n>
Refrigerant: <n></n>	
Setting of pressure safety device: <p> (bar)</p>	

<k></k>	PS	46 bar
<b>\</b>	TSmin	−20 °C
<m></m>	TSmax	150 °C
<n></n>		R32
<p></p>	·	44 bar

<Q> Bureau Veritas Italia S.p.A. Via Miramare 15, 20126 Milano (MI), Italy

Name and address of the Notified body that judged positively on compliance with the Pressure Equipment (Safety) Regulations: <Q>

DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN DAIKIN